

⚡ Specifications

Nominal Voltage(V)

12V

Nominal Capacity

20 hour rate	(0.6A	to	10.50V)	12Ah
5 hour rate	(2.04A	to	10.20V)	10.2Ah
1 hour rate	(6.6A	to	9.60V)	6.6Ah
1 C	(12A	to	9.60V)	6.4Ah

Weight

Approx. 4.0kg(8.8Lbs.)

Internal Resistance (at 1KHz)

Approx. 13 mΩ

Maximum Discharge Current for

5 seconds:180A

Charging Methods at 25°C(77°F)

Cycle use:

Charging Voltage 13.8 to 14.4V

Coefficient -5.0mV/°C/cell

Maximum Charging Current : 3.6A

Standby use:

Float Charging Voltage 13.5 to 13.8V

Coefficient -3.0mV/°C/cell

Operating Temperature Range

Charge -15°C(5°F) to 40°C(104°F)

Discharge -15°C(5°F) to 50°C(122°F)

Storage -15°C(5°F) to 40°C(104°F)

Charge Retention (shelf life) at 20°C(68°F)

1 month	92%
3 month	90%
6 month	80%

Case Material

ABS UL94 HB

Option: Flammability resistance of (UL94 V-0)

Design Life

7-10 Years.

Terminal

F1 or F2 (Faston Tab 187 or 250)



⚡ Dimensions

Length (L)

151±1 (5.94±0.04)

Width (W)



98±1 (3.86±0.04)

Height (H)


93±1 (3.66±0.04)

Overall Height (HT)


98±1 (3.86±0.04)




(v) FOR 12V BATTERY Discharge Time VS. Discharge Current (25°C)




Effect of Temperature on Capacity 25°C(77°F)




Capacity Retention Characteristic



Cycle Service Life



Trickle (or float) Service Life



- PERFORMANCE DATA

Discharge Rates in Watts to Various End Voltages at 25°C(77°F)

End Voltage		1.85V	1.80V	1.75V	1.70V	1.67V	1.65V	1.60V
Time								
5	min	61.2	69.4	74.3	78.0	79.8	81.7	84.8
10	min	40.4	46.4	50.4	53.4	54.8	55.3	56.8
15	min	27.8	34.2	38.2	41.3	42.2	43.2	44.2
30	min	16.8	19.7	21.8	23.3	23.8	24.3	24.8
60	min	13.1	14.1	14.6	14.9	15.1	15.2	15.3
120	min	7.58	8.03	8.32	8.57	8.65	8.75	8.86
180	min	5.25	5.60	5.85	6.05	6.12	6.21	6.28
240	min	4.37	4.62	4.82	4.97	5.03	5.10	5.18
300	min	3.88	4.03	4.15	4.27	4.32	4.36	4.43
600	min	2.23	2.32	2.38	2.45	2.47	2.50	2.54
1200	min	1.13	1.18	1.22	1.27	1.28	1.29	1.32

- Discharge Rates in Amperes to Various End Voltages at 25°C(77°F)

End Voltage		1.85V	1.80V	1.75V	1.70V	1.67V	1.65V	1.60V
Time								
5	min	32.6	38.4	42.1	45.1	46.4	47.7	50.3
10	min	20.9	24.3	26.6	28.5	29.1	29.6	30.4
15	min	18.2	19.6	20.8	21.7	22.0	22.3	22.9
30	min	10.9	11.7	12.1	12.5	12.6	12.8	13.0
60	min	7.02	7.53	7.76	7.97	8.05	8.12	8.21
120	min	3.63	3.92	4.10	4.25	4.31	4.36	4.42
180	min	2.57	2.78	2.94	3.05	3.09	3.13	3.18
240	min	2.09	2.27	2.39	2.46	2.49	2.52	2.56
300	min	1.92	2.00	2.06	2.11	2.13	2.16	2.20
600	min	1.09	1.14	1.18	1.21	1.22	1.24	1.26
1200	min	0.574	0.598	0.621	0.636	0.642	0.649	0.650

All data on the spec. sheet is an average value:

The tolerance range : $X < 6\text{min}$ (+15%~-15%), $6\text{min} \leq X < 10\text{min}$ (+12%~-12%), $10\text{min} \leq X < 60\text{min}$ (+8%~-8%), $X \geq 60\text{min}$ (+5%~-5%)

170818-1G