

ODYSSEY[®] BATTERY

ODP-AGM35 (ELT-AGM35)

Technical Data Sheet

Battery Type

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

Power & Performance

| | |
|--|----------|
| Voltage | 12V |
| Capacity (20-hour rate) | 59Ah |
| Capacity (10-hour rate) | 55Ah |
| Cold Cranking Amps (CCA, SAE J537) | 675A |
| PHCA - 5-second pulse current | 1200A |
| HCA | 900A |
| MCA | 770A |
| Reserve capacity | 110 mins |
| Short circuit current (using IEC method) | 1850A |
| Internal resistance at 20°C (using IEC method) | 4.3 mΩ |

Dimensions & Weight

| | |
|------------------------------|---------|
| Length | 241 mm |
| Width | 175 mm |
| Height (to top of terminals) | 218 mm |
| Height Container | 201 mm |
| Weight | 20.8 kg |

Temperature

| | |
|-----------------------------|----------------|
| Operating Temperature Range | -40°C to +60°C |
| Optimum Storage Temperature | +20°C |

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

Charging & self-discharge


| | |
|-----------------------------------|----------------|
| Type of charging curve | IUU |
| Charge voltage @+20°C | 14.4V to 14.8V |
| Self-discharge per month at +20°C | 1.25% |
| Self-discharge per month at +40°C | 5% |

Fitting, handling & storage

Can be mounted or stored in any orientation except inverted.
2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first.
Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).





Terminal Position



Terminal Type

SAE Terminals



ODP-AGM35
RIGHT POSITIVE
SAE TERMINALS

