

ODS-AGM40E (PC1100)

Technical Data Sheet

Battery Type

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

Power & Performance

Voltage	12V
Capacity (20-hour rate)	45Ah
Capacity (10-hour rate)	43Ah
Cold Cranking Amps (CCA, SAE J537)	500A
PHCA - 5-second pulse current	1100A
HCA	800A
MCA	650A
Reserve capacity	87 mins
Short circuit current (using IEC method)	2450A
Internal resistance at 20°C (using IEC method)	$5.1~\text{m}\Omega$

Dimensions & Weight

Length	249 mm
Width	97 mm
Height (to top of terminals)	206 mm
Height Container	196 mm
Weight	12.5 kg

Temperature

Operating Temperature Range	-40°C to +50°C
Optimum Storage Temperature	+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

Charging & self-discharge

Type of charging curve	IUU
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

Fitting, handling & storage


Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).




Terminal Position


• • - +

Terminal Type











PDF Generated at https://eu.odysseybattery.com 16/11/2021 12:49:20 Information correct at time of exporting PDF. Please check website for updates.

